

Wall mounting case AR-600



AR600 is the standard case for max. 8 REL/isp modules, ideal for medium size systems or multiple racks systems. AR600 systems are particularly suitable for small areas or on large sites, where it is preferable to have a number of small self-contained monitoring systems connected by a field bus to a remote Host system. AR600 is supplied fully wired, for 8 REL/isp modules and up to 12 ISP alarm outputs with (SPDT) relay rated at 3A 110 Vac.

GENERAL SPECIFICATION

12 (SPDT) 3A 110 Vac relays outputs, configurable even with isp technology
Standard serial line RS-485
Extensive libraries of ready-to-go configuration for the logic of the alarms.

Electrical Specification

Supply voltage	110-220 Vac
Supply fuse	1.6 A
Stabilised power supply output	13.75 or 27.5 Vdc
Overvoltage protection	± 50V.

Environmental Specification


Storage temperature	-40 to 85 °C
Operating temperature	-10 to 70 °C
Humidity range	90% R.H. n.c.

Mechanical Specification

Overall dimensions	600x345x373 mm
Mounting	3U-HE 19" Rack
Cabling	Screw terminals

Part number description

AR600



Sede Operativa: Via Lavoratori Autobianchi,1 20832 Desio (Mb) IT
Telefono +39 0362 629135 fax +39 0362 622531
www.oggionisas.com e-mail: info@oggionisas.com



Atex Notified